

# 2 colson SERIES


Capacity up to 325 lbs each

www.colsoncaster.com

## Standard Features

- Zinc plated finish is attractive and durable
- Full double ball hardened raceways for better performance and greater durability
- 3/8" hollow axle with lock nut
- Grease holes on wheel bearing for greater convenience
- "Colson 45" multi-temp grease lubricates in extreme hot and cold temperatures

## Modular Stem



### Standard Mounting:

Colson modular stem casters feature a 1/2" hollow rivet which will accept a wide variety of mounting stems (even a standard 1/2" bolt will work). You can supply the mounting fasteners or stems—we supply the casters.

## Performance Options

### Caster Brake

**Total Lock Brake** (See page 12)  
Locks wheel and swivel simultaneously. Fits 3 1/2", 4" and 5" swivel models. Field installable (Specify **BRK5**).

**Side Lock Brake** (See page 12)  
Available on all swivel models. Field installable (Specify **BRK1**).

### Fork Option

**NSF Listed** (See page 3)  
All models except thread guards and cast iron wheels (Specify **FSI**).

**Swivel Dust Cap** (See page 16)  
Specify **DC1**.

**Axle/Nut Options:**  
**AX1** Zerk Axle  
**AX2** Solid Axle  
**NT1** Thick lock nut



### Wheel Option

**Thread Guards** (See page 16)  
Available on many models. (Specify **TG1** for metal **TG2** for plastic).

## Wheel Selection



PERFORMA  
FLAT TREAD



PERFORMA  
ROUND TREAD



PERFORMA  
CONDUCTIVE FLAT



PERFORMA  
CONDUCTIVE ROUND



POLYOLEFIN



THERMO



THERMOTECH®



POLYURETHANE  
HI-TECH



CAST IRON



RUBBER HI-TECH



PHENOLIC

## 2 SERIES • Modular Stem • Capacity up to 325 lbs

Wheel Dia.	Tread Width	Capacity Each (Pounds)	Wheel Descriptions	Wheel Bearing	Stem Caster Models	Load Height	Swivel Radius	Weight (Pounds)	
2 1/2"	1 1/4"	125	Performa Rubber (Conductive Flat)	Ball	2.02250.445 COND	3 3/4	2 13/32	1 1/2	
		140	Performa Rubber (Flat tread)	Delrin	2.02250.441	3 3/4	2 13/32	1 1/2	
			Performa Rubber (Flat tread)	Ball	2.02250.445	3 3/4	2 13/32	1 1/2	
		200	Polyolefin	Delrin	2.02250.53	3 3/4	2 13/32	1 1/2	
			Polyolefin	Ball	2.02250.55	3 3/4	2 13/32	1 1/2	
		250	Polyurethane HI-TECH	Delrin	2.02250.91	3 3/4	2 13/32	1 1/4	
	Polyurethane HI-TECH		Ball	2.02250.95	3 3/4	2 13/32	1 1/4		
	300	Cast Iron	Sleeve	2.02250.12	3 3/4	2 13/32	2		
1 7/16"	300	Phenolic	Roller	2.02250.319	3 3/4	2 13/32	1 1/2		
3"	1 1/4"	150	Rubber HI-TECH	Plain	2.03350.42	4	2 21/32	2	
		200	Polyurethane HI-TECH	Plain	2.03350.92	4	2 21/32	2	
	Polyolefin		Delrin	2.03350.52	4	2 21/32	2		
	1 15/32"	300	Phenolic	Roller	2.03350.309	4	2 21/32	2 3/4	
3 1/2"	1 5/16"	210	Performa Rubber (Conductive Round)	Ball	2.03250.565 COND	4 9/16	2 29/32	2	
			Performa Rubber (Round tread)	Delrin	2.03250.561	4 9/16	2 29/32	2	
			Performa Rubber (Round tread)	Ball	2.03250.565	4 9/16	2 29/32	2	
	1 1/4"	225	Performa Rubber (Conductive Flat)	Ball	2.03250.445 COND	4 9/16	2 29/32	1 3/4	
			Polyolefin	Delrin	2.03250.53	4 9/16	2 29/32	1 3/4	
		230	Polyolefin	Ball	2.03250.55	4 9/16	2 29/32	1 3/4	
			Performa Rubber (Flat tread)	Delrin	2.03250.441	4 9/16	2 29/32	1 3/4	
		250	Performa Rubber (Flat tread)	Ball	2.03250.445	4 9/16	2 29/32	1 3/4	
			Polyurethane HI-TECH	Delrin	2.03250.91	4 9/16	2 29/32	1 3/4	
			Polyurethane HI-TECH	Ball	2.03250.95	4 9/16	2 29/32	1 3/4	
	300	Thermo	Plain	2.03250.52 HT	4 9/16	2 29/32	2 3/4		
		Cast Iron	Sleeve	2.03250.12	4 9/16	2 29/32	2 7/8		
	4"	1 1/4"	250	ThermoTech	Teflon	2.04250.613 H	5	3 7/32	3
				Performa Rubber (Conductive Flat)	Ball	2.04250.445 COND	5	3 7/32	2 1/8
275			Polyolefin	Delrin	2.04250.53	5	3 7/32	2 1/8	
			Polyolefin	Ball	2.04250.55	5	3 7/32	2 1/8	
			Polyurethane HI-TECH	Delrin	2.04250.91	5	3 7/32	1 7/8	
			Polyurethane HI-TECH	Ball	2.04250.95	5	3 7/32	1 7/8	
300		Performa Rubber (Flat tread)	Delrin	2.04250.441	5	3 7/32	2 1/8		
		Performa Rubber (Flat tread)	Ball	2.04250.445	5	3 7/32	2 1/8		
		Thermo	Plain	2.04250.52 HT	5	3 7/32	3 1/8		
		Cast Iron	Sleeve	2.04250.12	5	3 7/32	3 1/8		
5"	1 1/4"	250	ThermoTech	Teflon	2.05250.613 H	6 1/16	3 13/16	3	
			Performa Rubber (Conductive Flat)	Ball	2.05250.445 COND	6 1/16	3 13/16	2 3/4	
	1 5/16"	250	Performa Rubber (Conductive Round)	Ball	2.05250.565 COND	6 1/16	3 13/16	2 3/4	
			Performa Rubber (Round tread)	Delrin	2.05250.561	6 1/16	3 13/16	2 3/4	
			Performa Rubber (Round tread)	Ball	2.05250.565	6 1/16	3 13/16	2 3/4	
	1 1/4"	300	Polyolefin	Delrin	2.05250.53	6 1/16	3 13/16	2 1/4	
			Polyolefin	Ball	2.05250.55	6 1/16	3 13/16	2 1/4	
			Polyurethane HI-TECH	Delrin	2.05250.91	6 1/16	3 13/16	2 1/4	
		325	Polyurethane HI-TECH	Ball	2.05250.95	6 1/16	3 13/16	2 1/4	
			Cast Iron	Sleeve	2.05250.12	6 1/16	3 13/16	3 1/2	
			Performa Rubber (Flat tread)	Delrin	2.05250.441	6 1/16	3 13/16	2 1/2	
			Performa Rubber (Flat tread)	Ball	2.05250.445	6 1/16	3 13/16	2 1/2	
Thermo	Plain	2.05250.52 HT	6 1/16	3 13/16	3 1/4				

2 SERIES