


# 1 colson® SERIES

Capacity up to 75 lbs each

www.colsoncaster.com

## Straight Thread Stem



Swivel Cross Section  
Fork Leg Spacing 1 5/32"

### Standard Features

- Zinc plated finish is attractive and durable
- Full double ball hardened raceways for better performance and greater durability
- 5/16" shouldered axle with 1/4" nut
- "Colson 45" multi-temp grease lubricates in extreme hot and cold temperatures

## Performance Options

### Mounting Options

3/8" diameter— 24NF x  
1 1/16" long (Specify **MTG51**).

### Caster Brake

**Side Lock** (See page 12)  
Available on all 3" models. Field installable (Specify **BRK3**).

### Fork Option

**NSF Listed** (See page 3)  
All models except thread guards (Specify **FSI**).

### Standard Mounting (MTG55):

(3/8" diameter— 16UNC x  
1 1/4" long threaded 1 1/8").

### Wheel Option

**Thread Guards** – Available on many models. Brake & NSF options cannot be used with thread guards (Specify **TG1** for metal **TG2** for plastic).



## Wheel Selection



PERFORMA  
FLAT TREAD



POLYOLEFIN



POLYURETHANE  
HI-TECH



CUSHION  
RUBBER



HARD  
RUBBER

**IMPORTANT:** If caster stem is to be screwed into customer equipment, the customer must add a washer to the stem that will cover the incomplete threads and support the upper race. The stem shoulder must fit tightly against the customer equipment.

### 1 SERIES • Straight Thread Stem • Capacity up to 75 lbs

Wheel Dia.	Tread Width	Capacity Each (Pounds)	Wheel Descriptions	Wheel Bearing	Stem Caster Models	Load Height	Swivel Radius	Weight (Pounds)
1 5/8"	7/8"	60	Performa Rubber	Delrin	1.01654.441	2 1/2	1 3/4	3/8
		75	Polyolefin	Delrin	1.01654.52	2 1/2	1 3/4	3/8
2"	7/8"	75	Performa Rubber	Delrin	1.02254.441	2 11/16	1 15/16	3/8
			Polyolefin	Delrin	1.02254.52	2 11/16	1 15/16	3/8
			Cushion Rubber	Ball	1.02254.45	2 11/16	1 15/16	1/2
			Hard Rubber	Ball	1.02254.55	2 11/16	1 15/16	1/2
3"	7/8"	75	Performa Rubber	Delrin	1.03054.441	3 13/16	2 9/16	5/8
			Polyurethane HI-TECH	Delrin	1.03054.91	3 13/16	2 9/16	5/8
			Polyolefin	Delrin	1.03054.53	3 13/16	2 9/16	5/8