


1 colson SERIES

Capacity up to 145 lbs each www.colsoncaster.com

Standard Features

- Zinc plated finish is attractive and durable
- Full double ball hardened raceways for better performance and greater durability
- 5/16" shouldered axle with 1/4" nut
- "Colson 45" multi-temp grease lubricates in extreme hot and cold temperatures

Straight Thread Stem



Swivel Cross Section
Fork Leg Spacing 1 5/32"

Performance Options

Caster Brake

Side Lock (See page 12)
Available on all models. Field installable (Specify **BRK3**).

Fork Option

NSF Listed (See page 3)
All models except thread guards (Specify **FSI**).

Wheel Option

Thread Guards—Available on many models. Brake & NSF options cannot be used with thread guards (Specify **TG1** for metal **TG2** for plastic).



Standard Mounting:

(3/8" diameter—
16UNC x 1 1/2" long
threaded 1 3/8").

Wheel Selection



PERFORMA
FLAT TREAD



POLYOLEFIN



POLYURETHANE
HI-TECH

1 SERIES • Straight Thread Stem • Capacity up to 145 lbs

Wheel Dia.	Tread Width	Capacity Each (Pounds)	Wheel Descriptions	Wheel Bearing	Stem Caster Models	Load Height	Swivel Radius	Weight (Pounds)
3"	7/8"	100	Polyurethane HI-TECH	Delrin	1.03354.91	3 ³ / ₄	2 ¹³ / ₁₆	1 ¹ / ₈
		125	Performa Rubber	Delrin	1.03354.441	3 ³ / ₄	2 ¹³ / ₁₆	1 ¹ / ₈
			Polyolefin	Delrin	1.03354.53	3 ³ / ₄	2 ¹³ / ₁₆	1 ¹ / ₈
4"	7/8"	125	Polyurethane HI-TECH	Delrin	1.04354.91	4 ³ / ₄	3 ⁷ / ₁₆	1 ³ / ₈
		135	Performa Rubber	Delrin	1.04354.441	4 ³ / ₄	3 ⁷ / ₁₆	1 ³ / ₈
			Polyolefin	Delrin	1.04354.53	4 ³ / ₄	3 ⁷ / ₁₆	1 ³ / ₈
5"	7/8"	140	Polyurethane HI-TECH	Delrin	1.05354.91	5 ³ / ₄	4 ¹ / ₁₆	1 ⁵ / ₈
		145	Performa Rubber	Delrin	1.05354.441	5 ³ / ₄	4 ¹ / ₁₆	1 ⁵ / ₈
			Polyolefin	Delrin	1.05354.53	5 ³ / ₄	4 ¹ / ₁₆	1 ⁵ / ₈

IMPORTANT: If caster stem is to be screwed into customer equipment, the customer must add a washer to the stem that will cover the incomplete threads and support the upper race. The stem shoulder must fit tightly against the customer equipment.