

1 colson® SERIES


Capacity up to 145 lbs each

www.colsoncaster.com

Standard Features

- Zinc plated finish is attractive and durable
- Full double ball hardened raceways for better performance and greater durability
- 5/16" shouldered axle with 1/4" nut
- "Colson 45" multi-temp grease lubricates in extreme hot and cold temperatures

Square Stem




Swivel Cross Section
Fork Leg Spacing 1 5/32"

Performance Options

Mounting Options

Optional Square Stem: 2" long x 7/8" square with 1 mounting hole 17/64" diameter (Specify **MTG1**).



Caster Brake

Side Lock (See page 12)
Available on all models. Field installable (Specify **BRK3**).

Fork Option

NSF Listed (See page 3)
All models except thread guards (Specify **FSI**).



Wheel Option

Thread Guards – Available on many models. Brake & NSF options cannot be used with thread guards (Specify **TG1** for metal **TG2** for plastic).

Standard Mounting:

Designed for easy installation on the inside of angle iron legs or against flat surfaces. Stems may be bolted or riveted against any flat vertical surface. Standard Stem 2" long by 3/4" square with 3 mounting holes 17/64" diameter.

Wheel Selection



PERFORMA
FLAT TREAD



POLYOLEFIN



POLYURETHANE
HI-TECH

1 SERIES • Square Stem • Capacity up to 145 lbs

Wheel Dia.	Tread Width	Capacity Each (Pounds)	Wheel Descriptions	Wheel Bearing	Stem Caster Models	Load Height	Swivel Radius	Weight (Pounds)
3"	7/8"	100	Polyurethane HI-TECH	Delrin	1.03370.91	3 3/4	2 13/16	1 1/4
		125	Performa Rubber	Delrin	1.03370.441	3 3/4	2 13/16	1 1/4
			Polyolefin	Delrin	1.03370.53	3 3/4	2 13/16	1 1/4
4"	7/8"	125	Polyurethane HI-TECH	Delrin	1.04370.91	4 3/4	3 7/16	1 1/2
		135	Performa Rubber	Delrin	1.04370.441	4 3/4	3 7/16	1 1/2
			Polyolefin	Delrin	1.04370.53	4 3/4	3 7/16	1 1/2
5"	7/8"	140	Polyurethane HI-TECH	Delrin	1.05370.91	5 3/4	4 1/16	1 3/4
		145	Performa Rubber	Delrin	1.05370.441	5 3/4	4 1/16	1 3/4
			Polyolefin	Delrin	1.05370.53	5 3/4	4 1/16	1 3/4